



SKF 305702 C-2Z

Cam roller (yoke-type track roller) with flat outside surface, integral sealing and

These cam rollers (yoke-type track rollers) are designed to run on all types of tracks and to be used in cam drives, conveyor systems, etc. They are based on double row angular contact ball bearings. They have a thick-walled outer ring with a flat running surface and are supplied greased, sealed and ready-to-mount. A lubrication hole in the inner ring facilitates relubrication.

Technical specifications

Dimensions	
Outside diameter	40 mm
Bore diameter	15 mm
Width	15.9 mm
Shoulder/recess diameter inner ring	20.2 mm
Recess diameter outer ring	30.7 mm
Chamfer dimension	0.6 mm
Distance pressure points	21 mm
Functional outside diameter	40 mm

Calculation data	
Basic dynamic load rating	10.8 kN
Basic static load rating	5.7 kN
Fatigue load limit	0.24 kN
Maximum dynamic radial load	5.85 kN
Maximum static radial load	8.5 kN
Limiting speed	18000 r/min

Performance	
Basic dynamic load rating	10.8 kN
Basic static load rating	5.7 kN
Limiting speed	18000 r/min

Properties	
Bearing part	Complete track roller
Rolling elements	Balls
Number of rows	2
Outer ring profile	Cylindrical
Axial guidance of outer ring	Yes
Number of flanges, outer ring	0
Cage	With
Axial internal clearance	Normal
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Shield on both sides
Sealing type	Non-contact
Lubricant	Grease
Relubrication feature	With

Logistics	
Product net weight	0.103 kg
eClass code	23-05-08-03
UNSPSC code	31171531

SKF drawings