



SKF 24068 CC/W33

Spherical roller bearing with relubrication features

Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

Technical specifications

General	
Bore type	Cylindrical

Dimensions	
Bore diameter	340 mm
Deviation limits of mid-range bore diameter	-0.04..0 mm
Outside diameter	520 mm
Deviation limits of mid-range outside diameter	-0.05..0 mm
Width	180 mm
Deviation limits of ring width	-0.4..0 mm
Shoulder diameter of inner ring	377 mm
Shoulder/recess diameter of outer ring	453 mm
Width of lubrication groove	16.7 mm
Diameter of lubrication hole	9 mm
Chamfer dimension	5 mm
ISO tolerance class for dimensions	Normal

Abutment dimensions	
Diameter of shaft abutment	358 mm
Diameter of housing abutment	502 mm
Radius of fillet	4 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	3621 kN
Basic static load rating	6200 kN
Fatigue load limit	475 kN
Reference speed	750 r/min
Limiting speed	1100 r/min
Limiting value	0.33
Calculation factor	2
Calculation factor	3
Calculation factor	2

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	60 µm
Range of section height at outer ring of assembled bearing	100 µm
ISO tolerance class for geometrical tolerances	Normal

Radial internal clearance	
Minimum initial clearance	200 µm
Maximum initial clearance	310 µm

Performance	
Basic dynamic load rating	3621 kN
Basic static load rating	6200 kN
Reference speed	750 r/min
Limiting speed	1100 r/min

Properties	
Number of rows	2
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Radial internal clearance	CN
Tolerance class for dimensions	Normal
Tolerance class for run-out	Normal
Sealing	Without
Lubricant	None
Relubrication feature	With
Candidate for remanufacturing	Yes
Indicative carbon footprint for new product	494 kg CO ₂ e
Indicative carbon footprint for remanufactured product	173 kg CO ₂ e

Logistics	
Product net weight	137 kg
eClass code	23-05-09-11
UNSPSC code	31171510

SKF drawings

