



SKF SALKB 14 F

Rod end, maintenance-free, male thread

These SKF rod ends have an injection moulded sliding layer of PTFE FRP between the housing and the inner ring. This sliding contact surface combination is maintenance-free. The male thread is available with a left- (prefix SAL) or right-hand thread.

Technical specifications

General	
Maintenance	Maintenance-free
Sliding contact surface combination	Steel/PTFE FRP
Material, inner ring	Bearing steel
Sealing	Without
Attachment feature, rod end shank	Left-hand male thread
Dimensions	
Bore diameter	14 mm
Diameter head	37 mm
Width inner ring	19 mm
Thread	M 14
Width head	14.5 mm
Height shank end face - centre rod end eye	60 mm
Angle of tilt	16 °
Raceway diameter inner ring	25.4 mm
Length thread	36 mm
Length (height) housing	80 mm
Distance shank chamfer - centre rod end eye	18 mm
Chamfer dimension bore	0.3 mm
Bore diameter, bearing inner ring	14 mm
Outside diameter, housing eye	37 mm
Width, bearing inner ring	19 mm
Thread designation	M 14
Width, housing eye	14.5 mm
Centre height, housing (from end of shank)	60 mm
Housing length, total	80 mm
Calculation data	
Basic dynamic load rating	17 kN
Basic static load rating	25.5 kN
Specific dynamic load factor	50 N/mm ²
Material constant	530
Performance	
Basic dynamic load rating	17 kN
Basic static load rating	25.5 kN
Properties	
Sliding contact surface combination	Steel/PTFE FRP
Material, housing	Steel
Material, inner ring	Bearing steel
Maintenance	Maintenance-free
Attachment feature, rod end shank	Left-hand male thread
Sealing	Without
Logistics	
Product net weight	0.131 kg

eClass code	23-05-01-05
UNSPSC code	31171508

SKF drawings

