



## SKF 6201-2Z

### Deep groove ball bearing with seals or shields

Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

## Technical specifications

Dimensions	
Bore diameter	12 mm
Deviation limits of mid-range bore diameter	-0.007..0 mm
Outside diameter	32 mm
Deviation limits of mid-range outside diameter	-0.009..0 mm
Width	10 mm
Deviation limits of ring width	-0.06..0 mm
Shoulder diameter	18.45 mm
Recess diameter	27.34 mm
Chamfer dimension	0.6 mm
ISO tolerance class for dimensions	P6 and tighter width tolerance

Abutment dimensions	
Diameter of shaft abutment	16.2 mm
Diameter of shaft abutment	18.4 mm
Diameter of housing abutment	27.8 mm
Radius of shaft or housing fillet	0.6 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	7.28 kN
Basic static load rating	3.1 kN
Fatigue load limit	0.132 kN
Reference speed	50000 r/min
Limiting speed	26000 r/min
Minimum load factor	0.03
Calculation factor	12.2

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	4 μm
Maximum run-out of inner ring side face to the bore	7 μm
Maximum axial run-out of inner ring of assembled bearing	7 μm
Range of section height at outer ring of assembled bearing	7 μm
Perpendicularity of outer ring outside surface	4 μm
Maximum axial run-out of outer ring of assembled bearing	8 μm
ISO tolerance class for geometrical tolerances	P5

Performance	
Basic dynamic load rating	7.28 kN
Basic static load rating	3.1 kN
Reference speed	50000 r/min
Limiting speed	26000 r/min
SKF performance class	SKF Explorer

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without

Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Shield on both sides
Sealing type	Non-contact
Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	0.14 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	0.0375 kg
eClass code	23-05-08-01
UNSPSC code	31171504

**SKF drawings**