



SKF TLSD 125/WA2

SKF SYSTEM 24 single point lubricator

TLSD 125/WA2 is filled with SKF LGWA 2 grease for wide temperature ranges and extreme pressures, recommended for electric motors, conveyors, fans and pumps. Our electro-mechanical single point automatic lubricators are available in many configurations, pre-filled with SKF lubricants, both as battery or cable driven. Using automatic lubricators improves employee safety, increases machine reliability and optimizes maintenance operations.

Technical specifications

Performance	
Maximum pressure (P _{max})	5 bar
Properties	
Ambient temperature range	Array °C
Connecting thread (G)	G 1/4
Degree of protection (IP)	IP 65
Drive mechanism	Electro mechanical
Lubricant	LGWA 2
Lubricant description	Wide temperature range, extreme pressure, high load bearing grease
Lubricant operating temperature range	-30 to +140 °C
Lubricant quantity	125 ml
Maximum feed line length	3 m
Nominal emptying time	User adjustable: 1, 2, 3, 4, 6, 8, 10 and 12 months
Power source	Battery pack
Recommended applications	Fans and electric motors; Conveyor head and tail pulley bearings
Logistics	
Product net weight	0.56 kg
eClass code	23-06-10-14
UNSPSC code	15121902