



SKF GEZ 104 ES-2RS

Radial spherical plain bearing, requiring maintenance, sealed, inch sizes

Radial spherical plain bearings are designed to accommodate radial and combined radial and axial loads, and also misalignment. This specific design includes a steel/steel sliding contact surface combination and a double-lip contact seal on both sides. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Seal on both sides
Sealing type	Double-lip

Dimensions	
Bore diameter	31.75 mm
Outside diameter	50.8 mm
Width	27.762 mm
Width outer ring	23.8 mm
Angle of tilt	6 °
Raceway diameter inner ring	45.593 mm
Width annular lubrication groove at outer ring	4.4 mm
Width annular lubrication groove at inner ring	5 mm
Diameter lubrication hole (outer ring)	4 mm
Chamfer dimension bore	0.6 mm
Chamfer dimension outer ring	1 mm
Width, inner ring	27.762 mm
Width, outer ring	23.8 mm

Abutment dimensions	
Abutment diameter shaft	34.8 mm
Abutment diameter shaft	36.2 mm
Abutment diameter housing	44.8 mm
Abutment diameter housing	47 mm
Fillet radius shaft	0.6 mm
Fillet radius housing	1 mm

Calculation data	
Basic dynamic load rating	86.5 kN
Basic static load rating	260 kN
Specific dynamic load factor	100 N/mm ²
Specific static load factor	300 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	86.5 kN
Basic static load rating	260 kN

Properties	
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Radial internal clearance	CN

Sealing	Seal on both sides
Sealing type	Double-lip
Relubrication feature	With
Logistics	
Product net weight	0.214 kg
eClass code	23-05-01-06
UNSPSC code	31171515

SKF drawings