



SKF W 61907-2RS1

Stainless steel deep groove ball bearing with integral sealing

Stainless steel single row deep groove ball bearing with seals or shields on both sides, provide greater chemical and corrosion resistance. As with deep groove ball bearings generally, they are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

Technical specifications

Dimensions	
Bore diameter	35 mm
Outside diameter	55 mm
Width	10 mm
Shoulder diameter	42.2 mm
Recess diameter	42.2 mm
Recess diameter	52.15 mm
Chamfer dimension	0.6 mm

Abutment dimensions	
Diameter of shaft abutment	39 mm
Diameter of shaft abutment	42 mm
Diameter of housing abutment	52.5 mm
Radius of shaft or housing fillet	0.6 mm

Calculation data	
Basic dynamic load rating	9.36 kN
Basic static load rating	7.65 kN
Fatigue load limit	0.325 kN
Limiting speed	7500 r/min
Minimum load factor	0.03
Calculation factor	15.7

Performance	
Basic dynamic load rating	9.36 kN
Basic static load rating	7.65 kN
Limiting speed	7500 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Stamped stainless steel
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Stainless steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	0.26 kg CO ₂

Logistics	
Product net weight	0.072 kg
eClass code	23-05-08-01
UNSPSC code	31171504

