



SKF HK 0810

Drawn cup needle roller bearing with open ends

Drawn cup needle roller bearings are typically used in applications where the housing bore cannot be used as a raceway for a needle roller and cage assembly, but where a very compact and economical bearing arrangement is required. Owing to their large number of rollers, the bearings have a high load carrying capacity and stiffness.

Technical specifications

Dimensions	
Diameter under rollers	8 mm
Outside diameter	12 mm
Width	10 mm
Chamfer dimension drawn cup (outer ring)	0.4 mm
Bore diameter of needle roller complement	8 mm

Calculation data	
Basic dynamic load rating	3.69 kN
Basic static load rating	4.05 kN
Fatigue load limit	0.44 kN
Reference speed	19000 r/min
Limiting speed	22000 r/min

Associated products	
Inner ring IR series	IR 5x8x12
Radial shaft seal with a low cross-sectional height, single lip	G 8x12x3

Performance	
Basic dynamic load rating	3.69 kN
Basic static load rating	4.05 kN
Reference speed	19000 r/min
Limiting speed	22000 r/min

Properties	
Bearing part	Bearing without inner ring
Number of rows	1
Outer ring type	Drawn cup with open ends
Aligning feature	Without
Cage	Sheet steel
Number of flanges, outer ring	2
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.01 kg CO ₂ e

Logistics	
Product net weight	0.003 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings