



SKF SNL 218

Split plummer (pillow) block housing, SNL 2, 3, 5 and 6 series

SNL plummer (pillow) block housings are the most popular SKF bearing housings on the market, developed to be the first choice for design, quality and economy. They enable the incorporated bearings to achieve maximum service life with less need for maintenance. Different housing variants and seal designs are available, making the use of tailored housings virtually unnecessary and enabling cost-effective bearing arrangements to be made.

Technical specifications

Dimensions	
Diameter of bearing seat	160 mm
Tolerance class of bearing seat diameter	G7
Width of bearing seat	65 mm
Centre height of bearing seat	100 mm
Bore diameter	120 mm
Overall width	143 mm
Foot width	100 mm
Thread of relubrication holes	1/8-27 NPSF
Overall height	192 mm
Foot height	35 mm
Overall length	345 mm
Distance between attachment bolts	290 mm
Length of attachment bolt hole	28 mm
Width of attachment bolt hole	22 mm
Inside width between seal grooves	112 mm
Width of seal groove	5 mm
Distance to seal groove back face	9 mm
Width at bore diameter	13 mm
Diameter of seal groove	128.5 mm
Distance between dowel pins	317 mm
Axial offset of dowel pins	35 mm
Diameter of dowel pins	8 mm
Centre height (pillow block)	100 mm
Centre distance between bolt holes	290 mm
Attachment bolt diameter	20 mm

Calculation data	
Breaking load at 0° load angle (if the housing is not supported over its entire base)	430 kN
Breaking load at 55° load angle	550 kN
Breaking load at 90° load angle	340 kN
Breaking load at 120° load angle	250 kN
Breaking load at 150° load angle	215 kN
Breaking load at 180° load angle	275 kN
Breaking load, axial	180 kN
Load to reach yield point at 120° load angle	400 kN
Load to reach yield point at 150° load angle	230 kN
Load to reach yield point at 180° load angle	200 kN

Materials	
Housing material	Cast iron
Corrosion protection	Paint - in accordance with ISO 12944-2, corrosivity category C2

Mounting information	
Recommended diameter of attachment bolts	20 mm
Recommended tightening torque for attachment bolts	385 N·m

Size of cap bolts	M 16x90
Tightening torque for cap bolts	150 N·m
Initial grease fill, 20%	260 g
Initial grease fill, 40%	430 g

Included products	
Grease fitting	AH 1/8-27 PTF

Properties	
Housing type	Plummer/pillow block
Housing configuration	Two-piece
Mounting arrangement	Through shaft/Shaft end
Number of bolt holes for fasteners	2
Material, housing	Cast iron
Bearing housing seal type	Without
Housing lubrication feature/possibility	Grease

Logistics	
Product net weight	12.1 kg
eClass code	23-05-17-01
UNSPSC code	31171519





