



SKF NJ 2228 ECML

Single row cylindrical roller bearing, NJ design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and one on the inner ring, NJ design bearings can accommodate axial displacement in one direction. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	140 mm
Outside diameter	250 mm
Width	68 mm
Shoulder diameter of inner ring	179 mm
Shoulder diameter of outer ring	216.7 mm
Raceway diameter of inner ring	169 mm
Chamfer dimension	3 mm
Chamfer dimension	3 mm
Permissible axial displacement	4.4 mm

Abutment dimensions	
Diameter of spacer sleeve	154 mm
Diameter of spacer sleeve	165 mm
Diameter of shaft abutment	182 mm
Diameter of housing abutment	235 mm
Radius of fillet	2.5 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	655 kN
Basic static load rating	830 kN
Fatigue load limit	93 kN
Reference speed	2800 r/min
Limiting speed	4800 r/min
Minimum load factor	0.3
Limiting value	0.3
Calculation factor	0.4

Associated products	
Angle ring	HJ 2228 EC

Performance	
Basic dynamic load rating	655 kN
Basic static load rating	830 kN
Reference speed	2800 r/min
Limiting speed	4800 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Axial displacement capability	In one direction
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Machined brass
Number of flanges, outer ring	2
Number of flanges, inner ring	1

Loose flange	None
Radial internal clearance	CN
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	55 kg CO ₂ e

Logistics	
Product net weight	15.3 kg
eClass code	23-05-09-01
UNSPSC code	31171505

SKF drawings