



SKF LAGG 18M

Grease pump for use on drums

SKF manual grease pump LAGG 18M is designed to supply grease at high pressure from a 18 kg drum. This is useful when large housings have to be filled or when numerous points have to be lubricated. It is also possible to top up centralised lubrication system reservoirs.

Technical specifications

Dimensions	
Suitable drum inner diameter	Array mm
Suitable drum inside height (max)	420 mm
Performance	
Maximum pressure (P_{max})	50 MPa
Properties	
Recommended applications	grease pump for drums or pails designed for high pressure applications; can be connected directly on greasing points; suitable for filling centralised lubricating grease systems
For type/size of grease drum	18 kg grease pail
Operation	air operated grease pump
Mobility	stationary
NLGI class of lubricant (max)	2
Connection	greasing point: DIN 71412
Air pressure	Array bar
Volume per stroke	1.6 ml
Hose	Yes, 3.5 Meter
Optional Trolley	LAGT 18 - 50
Power source	manual
Material	steel, rubber hose
Material handle	steel with plastic grip
Ambient temperature range	Array °C
Recommended storage temperature	Array °C
Relative humidity	< 65 %
Content	grease pump with pump handle, drum cover plate, drum followerplate, high pressure hose
Logistics	
Product net weight	5.81 kg
eClass code	23-06-91-06
UNSPSC code	15121902