



SKF FYTB 30 FM

Oval flanged ball bearing unit with eccentric locking, cast iron housing, ISO

These oval flanged ball bearing units are compliant with ISO standards. They consist of an insert bearing, with a narrow inner ring and eccentric locking, and are intended primarily for use in applications where the direction of rotation is constant. The bearing is mounted in a cast iron housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

Technical specifications

General	
Compliance with standard	ISO
Purpose specific	For material handling applications
Material, housing	Cast iron
Sealing, bearing	Seal on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Optional end cover
Coating	Without

Dimensions	
Bore diameter	30 mm
Outer diameter of inner ring	39.7 mm
Outside diameter of locking ring	44.1 mm
Width of housing	32.5 mm
Flange width	13 mm
Depth of centring recess	3.2 mm
Width including end cover	22.5 mm
Width of inner ring	23.8 mm
Overall bearing width	35.7 mm
Distance from locking device side face to thread centre	5.95 mm
Top external diameter	77 mm
Base external diameter	83 mm
Diameter of housing centering recess	76.2 mm
Overall height	141.5 mm
Centre distance between bolt holes	116.5 mm
Overall length	83 mm
Diameter of attachment bolt hole	11.5 mm
Distance from locking device side face to raceway centre	26.7 mm
Overall width	46.7 mm
Housing thread for grease fitting	1/4-28 UNF
Axial position of the housing thread	21 mm
Angular position of the housing thread	45 °
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of grease fitting	1/4-28 SAE-LT
Distance of dowel pins	98.5 mm
Axial offset of dowel pins	12.5 mm
Recommended diameter for dowel pins	2 mm
Attachment bolt diameter	10 mm
Shaft diameter	30 mm
Housing overall width	32.5 mm
Width, total	46.7 mm
Bearing width, total	35.7 mm

Calculation data	
Basic dynamic load rating	19.5 kN
Basic static load rating	11.2 kN
Fatigue load limit	0.475 kN

Limiting speed	6300 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M8x1
Hexagonal key size for set screw	4 mm
Recommended tightening torque for set screw	6.5 N·m
Recommended diameter for attachment bolts, mm	10 mm
Recommended diameter for attachment bolts, inch	0.375 in

Performance	
Basic dynamic load rating	19.5 kN
Basic static load rating	11.2 kN
Limiting speed	6300 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Housing type	Flanged
Flanged housing type	Oval
Number of bolt holes for fasteners	2
Fastening bolt hole type	Plain
Retaining feature, inner ring	Eccentric collar
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal on both sides
Sealing type	Contact, standard
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics	
Product net weight	0.868 kg
eClass code	23-05-08-02
UNSPSC code	31171536

SKF drawings

