

SKF LAGH 400

Manual operated grease gun, one handed

The SKF Grease Gun LAGH 400 is ideal for usage in agricultural, industrial and construction industries and for private use. The grease gun is equipped with a filler nipple and air-release valve for easy re-filling by filler or grease pumps. It can also be suitable for usage with grease cartridges. The ergonomic design for one handed operation, the flexible high pressure hose and the possibility to mount the hose in both horizontal and vertical position makes this grease gun very versatile and easy to use.

Technical specifications

Dimensions	
Length (L)	370 mm
Performance	
Maximum pressure (P_{max})	300 bar
Volume per stroke	0.46 ml
Properties	
Can be filled with Grease filler pump	Yes, with SKF LAGF 18 or LAGF 50
Extension pipe	Optional
Filling connection	DIN 1283
Grease supply	Loose or Cartridge
Hose	Yes, 300mm
NLGI class of lubricant (max)	2
Operation	One handed
Pipe/Hose thread connection	M10x1
Recommended applications	For manual filling of greasing points in industrial, construction and agricultural applications
Reservoir volume	500 ml
Suitable for grease nipples	Standard nipples as per DIN 71412
Type	Manual grease gun
Use of standard grease cartridges	Yes, type DIN 1284
Logistics	
Product net weight	1.28 kg
eClass code	23-06-91-06
UNSPSC code	15121902