



SKF SNL 506-605

Split plummer (pillow) block housing, SNL 2, 3, 5 and 6 series

SNL plummer (pillow) block housings are the most popular SKF bearing housings on the market, developed to be the first choice for design, quality and economy. They enable the incorporated bearings to achieve maximum service life with less need for maintenance. Different housing variants and seal designs are available, making the use of tailored housings virtually unnecessary and enabling cost-effective bearing arrangements to be made.

Technical specifications

Dimensions	
Diameter of bearing seat	62 mm
Tolerance class of bearing seat diameter	G7
Width of bearing seat	32 mm
Centre height of bearing seat	50 mm
Bore diameter	36.5 mm
Overall width	77 mm
Foot width	52 mm
Thread of relubrication holes	1/8-27 NPSF
Overall height	89 mm
Foot height	22 mm
Overall length	185 mm
Distance between attachment bolts	150 mm
Length of attachment bolt hole	20 mm
Width of attachment bolt hole	15 mm
Inside width between seal grooves	55 mm
Width of seal groove	5 mm
Distance to seal groove back face	7.5 mm
Width at bore diameter	10 mm
Diameter of seal groove	44.5 mm
Distance between dowel pins	172 mm
Axial offset of dowel pins	19 mm
Diameter of dowel pins	5 mm
Centre height (pillow block)	50 mm
Centre distance between bolt holes	150 mm
Attachment bolt diameter	12 mm

Calculation data	
Breaking load at 0° load angle (if the housing is not supported over its entire base)	130 kN
Breaking load at 55° load angle	170 kN
Breaking load at 90° load angle	100 kN
Breaking load at 120° load angle	80 kN
Breaking load at 150° load angle	65 kN
Breaking load at 180° load angle	85 kN
Breaking load, axial	55 kN
Load to reach yield point at 120° load angle	150 kN
Load to reach yield point at 150° load angle	85 kN
Load to reach yield point at 180° load angle	75 kN

Materials	
Housing material	Cast iron
Corrosion protection	Paint - in accordance with ISO 12944-2, corrosivity category C2

Mounting information	
Recommended diameter of attachment bolts	12 mm
Recommended tightening torque for attachment bolts	80 N·m

Size of cap bolts	M10x40
Tightening torque for cap bolts	50 N·m
Initial grease fill, 20%	25 g
Initial grease fill, 40%	40 g

Included products	
Grease fitting	AH 1/8-27 PTF

Properties	
Housing type	Plummer/pillow block
Housing configuration	Two-piece
Mounting arrangement	Through shaft/Shaft end
Number of bolt holes for fasteners	2
Material, housing	Cast iron
Bearing housing seal type	Without
Housing lubrication feature/possibility	Grease

Logistics	
Product net weight	1.99 kg
eClass code	23-05-17-01
UNSPSC code	31171519





