

SKF TMIP 30-60

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Width of grip internal	Array mm
Workpiece width (max)	TMIP E30-40: >35 mm; TMIP E45-60: >64 mm
Housing depth (max)	TMIP E30-40: 97 mm; TMIP E45-60:102 mm
Needed free depth behind workpiece	TMIP E30-40: 11.5 mm; TMIP E45-60:15 mm
Extractor Hexagonal head size	All: 19 mm
Total extractor length	TMIP E30-40: 143 mm; TMIP E45-60:155 mm
Slide hammer total length	557 mm
Case dimensions (l x h x w)	530 x 85 x 180 mm

Свойства	
Рекомендуемые применения	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit inside a housing
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Нет
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Нет
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Нет
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Да
Suitable for bearing type(s)	All
Dismounting force generation	Sliding hammer
Special features	With unique spring-loaded grip system for easy operation
Total number of extractors in kit	2x : TMIP E30-40, TMIP E45-60
Slide hammer weight(s)	2.05 kg
Total number of sliding hammers in kit	1x :TMIP S2
Материал	Medium carbon steels and alloy engineering steels, hardened and tempered
Material handle	Opener handle: steel, Slidehammer: thermoplastic elastomer
Покрытие	Zinc coated
Content	2x Extractors size E30-40 and E45-60;1x slidehammer, size S2;1x Printed Instructions for Use (language free);1x Carrying case (size X)

Логистика	
Масса нетто	5.38 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712