



SKF N 317 ECP

Single row cylindrical roller bearing, N design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the inner ring and no flanges on the outer ring, N design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	85 mm
Outside diameter	180 mm
Width	41 mm
Shoulder diameter of inner ring	117 mm
Raceway diameter of outer ring	160 mm
Chamfer dimension	3 mm
Chamfer dimension	3 mm
Permissible axial displacement	2.3 mm

Abutment dimensions	
Diameter of spacer sleeve	99 mm
Diameter of spacer sleeve	157 mm
Diameter of housing abutment	163 mm
Diameter of housing abutment	166 mm
Radius of fillet	2.5 mm
Radius of fillet	2.5 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	340 kN
Basic static load rating	335 kN
Fatigue load limit	41.5 kN
Reference speed	4000 r/min
Limiting speed	4800 r/min
Minimum load factor	0.12
Limiting value	0.2
Calculation factor	0.6

Performance	
Basic dynamic load rating	340 kN
Basic static load rating	335 kN
Reference speed	4000 r/min
Limiting speed	4800 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Non-metallic
Number of flanges, outer ring	0
Number of flanges, inner ring	2
Loose flange	None
Radial internal clearance	CN
Tolerance class	Normal

Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	16.4 kg CO ₂ e

Logistics	
Product net weight	4.54 kg
eClass code	23-05-09-01
UNSPSC code	31171505

SKF drawings