



SKF 70 VA R

V-ring seal, VA design, global standard, interchangeable with VR1 design

V-ring seals (V-rings) are all-rubber, axial shaft seals. They offer an easy-to-install solution for rotating shaft applications, including use as a secondary seal in highly contaminated environments. The VA design includes a standard cross section with a straight back side face. Being the most common type of V-rings, VA seals are typically used to protect bearing arrangements in gearboxes, electric motors and drives.

Technical specifications

General	
Design	VA
Lip material	Nitrile rubber (NBR)
Dimensions	
Shaft diameter range (over)	68 mm
Shaft diameter range (incl.)	73 mm
Seal inside diameter, free state	63 mm
Nominal seal width	11 mm
Seal seat width	6.8 mm
Nominal seal height	6 mm
Radial gap (twice)	3 mm
	$D_{₁ \text{ max.}} = d_{₁} + 2x$
Radial distance (twice)	18 mm
	$D_{\text{min.}} = d_{₁} + 2y$
Seal fitted width	9 mm
Shaft diameter, minimum	68 mm
Shaft diameter, maximum	73 mm
Seal width	11 mm
Application and operating conditions	
Operating temperature	-40 °C
Operating temperature	100 °C
Properties	
Design	VA
Sealing lip material	Nitrile rubber (NBR)
Logistics	
Product net weight	0.0107 kg
eClass code	23-07-08-01
UNSPSC code	31181602

SKF drawings