



SKF 6229

Radial shaft seal with metal case, SKF Wave lip and auxiliary, contacting lip, for oil

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. CRWA5 seals are designed with a metal case, an SKF WAVE lip made of elastomer with higher pumping rate to reduce heat generation. The seal also has a garter spring and a non-contacting auxiliary lip optimizes the sealing against the shaft.

Technical specifications

General	
Type of outside diameter	Metal-cased with sealant coating on the outside diameter
Lip material	Nitrile rubber (NBR)
Seal design	CRWA5

Dimensions	
Shaft diameter	15.88 mm
Housing bore diameter	28.55 mm
Seal width	9.53 mm

Application and operating conditions	
Operating temperature	-40 °C
Operating temperature	100 °C
Circumferential speed	3.2 m/s
Rotational speed	3838 r/min
Pressure differential	0.35 N/mm ²

Associated products	
SKF Speedi-Sleeve	99058

Performance	
Limiting speed	3838 r/min
Maximum operating temperature	100 °C
Minimum operating temperature	-40 °C
Permissible circumferential speed	3.2 m/s
Rotational speed	3838 r/min

Properties	
Design	CRWA5
Auxiliary lip	Yes
Sealing lip material	Nitrile rubber (NBR)
Type of outside diameter	Metal-cased with sealant coating on the outside diameter
Unit system	Inch

Logistics	
Product net weight	0.008 kg
eClass code	23-07-08-01
UNSPSC code	31181602

SKF drawings

