

SKF HK 1522

Drawn cup needle roller bearing with open ends

Drawn cup needle roller bearings are typically used in applications where the housing bore cannot be used as a raceway for a needle roller and cage assembly, but where a very compact and economical bearing arrangement is required. Owing to their large number of rollers, the bearings have a high load carrying capacity and stiffness.



Technical specifications

Dimensions	
Diameter under rollers	15 mm
Outside diameter	21 mm
Width	22 mm
Chamfer dimension drawn cup (outer ring)	0.8 mm
Bore diameter of needle roller complement	15 mm

Calculation data	
Basic dynamic load rating	13 kN
Basic static load rating	20 kN
Fatigue load limit	2.28 kN
Reference speed	15000 r/min
Limiting speed	16000 r/min

Associated products	
Inner ring IR series	IR 12x15x22.5
Inner ring LR series	LR 12x15x22.5
Radial shaft seal with a low cross-sectional height, single lip	G 15x21x3
Radial shaft seal with a low cross-sectional height, double lip	SD 15x21x3

Performance	
Basic dynamic load rating	13 kN
Basic static load rating	20 kN
Reference speed	15000 r/min
Limiting speed	16000 r/min

Properties	
Bearing part	Bearing without inner ring
Number of rows	2
Outer ring type	Drawn cup with open ends
Aligning feature	Without
Cage	Sheet steel
Number of flanges, outer ring	2
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	With
Indicative carbon footprint for new product	0.07 kg CO ₂ e

Logistics	
Product net weight	0.0197 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

