



SKF HK 1616

Drawn cup needle roller bearing with open ends

Drawn cup needle roller bearings are typically used in applications where the housing bore cannot be used as a raceway for a needle roller and cage assembly, but where a very compact and economical bearing arrangement is required. Owing to their large number of rollers, the bearings have a high load carrying capacity and stiffness.

Technical specifications

Dimensions	
Diameter under rollers	16 mm
Outside diameter	22 mm
Width	16 mm
Chamfer dimension drawn cup (outer ring)	0.8 mm
Bore diameter of needle roller complement	16 mm

Calculation data	
Basic dynamic load rating	10.5 kN
Basic static load rating	15.6 kN
Fatigue load limit	1.8 kN
Reference speed	14000 r/min
Limiting speed	16000 r/min

Associated products	
Inner ring IR series	IR 12x16x16
Radial shaft seal with a low cross-sectional height, single lip	G 16x22x3
Radial shaft seal with a low cross-sectional height, double lip	SD 16x22x3

Performance	
Basic dynamic load rating	10.5 kN
Basic static load rating	15.6 kN
Reference speed	14000 r/min
Limiting speed	16000 r/min

Properties	
Bearing part	Bearing without inner ring
Number of rows	1
Outer ring type	Drawn cup with open ends
Aligning feature	Without
Cage	Sheet steel
Number of flanges, outer ring	2
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.06 kg CO ₂

Logistics	
Product net weight	0.0154 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

