



## SKF 29422 E

### Spherical roller thrust bearing with stamped steel cage

Spherical roller thrust bearings accommodate very heavy axial and considerable radial loads. They have the highest load rating of all thrust bearings, enabling compact, high power density bearing arrangements. By combining two or more spherical roller thrust bearings, it is possible to create a bearing arrangement that is either self-aligning, allowing misalignment of the shaft, or very stiff.

## Technical specifications

Dimensions	
Bore diameter	110 mm
Outside diameter	230 mm
Height	73 mm
Outside diameter of shaft washer end side face	199 mm
Shoulder diameter outer ring	156 mm
Width shaft washer or length of shaft washer bore diameter that fits on shaft (bearings with a stamped steel cage)	47 mm
Height shaft washer + cage	64.7 mm
Height housing washer	34.7 mm
Distance from shaft washer end side face to pressure point	69 mm
Chamfer dimension shaft washer	3 mm

Abutment dimensions	
Diameter of shaft abutment	165 mm
Abutment diameter of spacer ring	120.5 mm
Outside diameter of spacer ring	129 mm
Diameter of housing abutment	193 mm
Fillet radius	2.5 mm

Calculation data	
Basic dynamic load rating	1180 kN
Basic static load rating	3000 kN
Fatigue load limit	325 kN
Reference speed	1600 r/min
Limiting speed	2800 r/min
Minimum axial load factor	0.86

Performance	
Basic dynamic load rating	1180 kN
Basic static load rating	3000 kN
Reference speed	1600 r/min
Limiting speed	2800 r/min
SKF performance class	SKF Explorer

Properties	
Locating feature, housing washer	None
Bore type	Cylindrical
Cage	Sheet metal
Tolerance class	Normal
Indicative carbon footprint for new product	47.9 kg CO <sub>2</sub>

Logistics	
Product net weight	13.3 kg
eClass code	23-05-11-03
UNSPSC code	31171507

**SKF drawings**

