



SKF SIKAC 16 M

Rod end, requires maintenance, female thread

These SKF rod ends contain a spherical plain bearing with a steel/bronze sliding contact surface combination. The bearing requires maintenance, sizes 6 and larger can be relubricated via a grease fitting in the housing and via the shank. The female thread is available with a left- (prefix SIL) or right-hand thread.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/bronze
Material, inner ring	Bearing steel
Sealing	Without
Attachment feature, rod end shank	Right-hand female thread

Dimensions	
Bore diameter	16 mm
Diameter head	43 mm
Width inner ring	21 mm
Thread	M 16
Width head	15.5 mm
Height shank end face - centre rod end eye	64 mm
Angle of tilt	15 °
Raceway diameter inner ring	28.575 mm
Housing diameter shank	22 mm
Housing diameter shank	29 mm
Length thread	24 mm
Length (height) housing	86 mm
Length wrench flat	8 mm
Distance shank chamfer - centre rod end eye	21 mm
Size wrench	22 mm
Chamfer dimension bore	0.3 mm
Bore diameter, bearing inner ring	16 mm
Outside diameter, housing eye	43 mm
Width, bearing inner ring	21 mm
Thread designation	M 16
Width, housing eye	15.5 mm
Centre height, housing (from end of shank)	64 mm
Housing length, total	86 mm

Calculation data	
Basic dynamic load rating	21.6 kN
Basic static load rating	29 kN
Specific dynamic load factor	50 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	21.6 kN
Basic static load rating	29 kN

Properties	
Sliding contact surface combination	Steel/bronze
Material, housing	Steel
Material, inner ring	Bearing steel
Maintenance	Relubrication required
Attachment feature, rod end shank	Right-hand female thread

Sealing	Without
---------	---------

Logistics	
Product net weight	0.227 kg
eClass code	23-05-01-05
UNSPSC code	31171508

SKF drawings

