



## SKF 3211 A-2Z/MT33

Double row angular contact ball bearing with seals or shields

Double row angular contact ball bearings, with seals or shields, correspond to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. Depending on the sealing execution, they can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

### Technical specifications

Dimensions	
Bore diameter	55 mm
Outside diameter	100 mm
Width	33.3 mm
Contact angle	30 °

  

Performance	
Basic dynamic load rating	61 kN
Basic static load rating	52 kN
Reference speed	6300 r/min
Limiting speed	6300 r/min
SKF performance class	SKF Explorer

  

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Shield on both sides
Sealing type	Non-contact
Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	3.4 kg CO <sub>2</sub>

  

Logistics	
Product net weight	0.942 kg
eClass code	23-05-08-03
UNSPSC code	31171531