



SKF 32038 X

Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

Technical specifications

General	
Dimension series	4FD

Dimensions	
Bore diameter	190 mm
Outside diameter	290 mm
Bearing width, total	64 mm
Shoulder diameter of inner ring	240.48 mm
Width of inner ring	64 mm
Width of outer ring	48 mm
Chamfer dimension of inner ring	3 mm
Chamfer dimension of outer ring	2.5 mm
Distance side face to pressure point	62 mm
Width, total	64 mm
Width, inner ring	64 mm
Width, outer ring	48 mm
Contact angle	16.4 °

Abutment dimensions	
Diameter of shaft abutment	210 mm
Diameter of shaft abutment	205.5 mm
Diameter of housing abutment	257 mm
Diameter of housing abutment	276.5 mm
Diameter of housing abutment	279 mm
Minimum width of space required in housing on large side face	10 mm
Minimum width of space required in housing on small side face	16 mm
Radius of shaft fillet	3 mm
Radius of housing fillet	2.5 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	806 kN
Basic static load rating	1200 kN
Fatigue load limit	112 kN
Reference speed	1600 r/min
Limiting speed	2000 r/min
Limiting value	0.44
Calculation factor	1.4
Calculation factor	0.8

Performance	
Basic dynamic load rating	806 kN
Basic static load rating	1200 kN
Reference speed	1600 r/min
Limiting speed	2000 r/min
SKF performance class	SKF Explorer

Properties	

Bearing part	Complete bearing
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	53.1 kg CO ₂ e

Logistics	
Product net weight	14.8 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings