



SKF 2307 EKTN9/C3

Self-aligning ball bearing with tapered bore

Self-aligning ball bearings, with a tapered bore, have two rows of balls, a common sphered raceway in the outer ring and two deep uninterrupted raceway grooves in the inner ring. They are insensitive to angular misalignment of the shaft relative to the housing, which can be caused, for example, by shaft deflection. The tapered bore facilitates ease of mounting via adapter sleeves or withdrawal sleeves.

Technical specifications

Dimensions	
Bore diameter	35 mm
Outside diameter	80 mm
Width	31 mm

Performance	
Basic dynamic load rating	39.7 kN
Basic static load rating	11.2 kN
Reference speed	16000 r/min
Limiting speed	12000 r/min

Properties	
Retaining feature, inner ring	None
Locating feature, bearing outer ring	Without
Number of rows	2
Bore type	Tapered 1:12
Cage	Non-metallic
Radial internal clearance	C3
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	2.3 kg CO ₂ e

Logistics	
Product net weight	0.638 kg
eClass code	23-05-08-06
UNSPSC code	31171532