



## SKF H 3132

Adapter sleeve with KM lock nut and MB lock washer, metric dimensions

Adapter sleeves are the most commonly used components for locating bearings with a tapered bore onto a cylindrical seat as they can be used on plain shafts or stepped shafts. They are slit and are supplied complete with a KM lock nut and a MB lock washer.

### Technical specifications

| Dimensions                           |             |
|--------------------------------------|-------------|
| Bore diameter                        | 140 mm      |
| Outside diameter small taper         | 160 mm      |
| Outside diameter lock nut            | 210 mm      |
| Width                                | 119 mm      |
| Width lock nut                       | 25 mm       |
| Width lock nut including lock washer | 27.5 mm     |
| Thread                               | M160x3      |
| External taper                       | 1:12        |
| Thread designation                   | M160x3      |
| Included products                    |             |
| Lock nut                             | KM 32       |
| Locking device                       | MB 32       |
| Associated products                  |             |
| Hydraulic nut                        | HMV 32E     |
| Properties                           |             |
| Taper                                | 1:12        |
| Holes for oil injection              | Without     |
| Logistics                            |             |
| Product net weight                   | 7.44 kg     |
| eClass code                          | 23-11-07-05 |
| UNSPSC code                          | 31163218    |

**SKF drawings**