

SKF 51100

Single direction thrust ball bearing

Single direction thrust ball bearings can accommodate axial loads in one direction. They must not be subjected to any radial load. Their separable components facilitate mounting/dismounting and maintenance inspections. Many of the components are interchangeable. The shaft washers have a ground bore that enables an interference fit.



Technical specifications

Dimensions	
Bore diameter	10 mm
Outside diameter	24 mm
Height	9 mm
Outside diameter shaft washer	24 mm
Inner diameter housing washer	11 mm
Chamfer dimension washer	0.3 mm

Abutment dimensions	
Abutment diameter shaft	19 mm
Abutment diameter housing	15 mm
Fillet radius	0.3 mm

Calculation data	
Basic dynamic load rating	8.71 kN
Basic static load rating	12.2 kN
Fatigue load limit	0.45 kN
Reference speed	9500 r/min
Limiting speed	13000 r/min
Minimum load factor	0.001

Performance	
Basic dynamic load rating	8.71 kN
Basic static load rating	12.2 kN
Reference speed	9500 r/min
Limiting speed	13000 r/min

Properties	
Axial load capability	Single-direction
Number of rows	1
Cage	Sheet metal
Housing washer type	Flat
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Indicative carbon footprint for new product	0.07 kg CO ₂

Logistics	
Product net weight	0.02 kg
eClass code	23-05-10-01
UNSPSC code	31171507

SKF drawings