



SKF LGHQ 2/18

Electric motor bearing grease

A mineral oil based grease using a di-urea thickener. It is suitable for electric motors and similar applications. It is specifically designed for usage with single point lubricators.

Technical specifications

Dimensions	
Corrosion protection, Emcor, ISO 11007, Distilled water	0-0

Performance	
Suitable for High load applications	●●●○○
Suitable for Vertical shaft applications	●●●○○
Suitable for applications with Oscilating movements	●●○○○
Suitable for applications with Severe vibrations	●○○○○
Suitable for applications that require Rust protection	●●●●○
Suitable for applications that require Water resistance	●●●●●
Suitable for applications that require Frequent start-up	●●●●○
Operating temperature range	Array °C
Load Range	Low - Medium C/P > 8
Speed Range	Medium - High
Dropping point (min) ISO 2176	260 °C
Penetration DIN ISO 2137, Worked, 60 strokes (10 ⁻¹ mm)	265 - 295
Penetration DIN ISO 2137, Prolonged (max.), 100 000 strokes, 10 ⁻¹ mm	385 max.
Mechanical stability - Roll stability, ASTM D1831 (max.) 50 hrs at 80°C, 10 ⁻¹ mm	385 max.
Mechanical stability, V2F test, 144 hrs	-
Corrosion protection, Emcor, ISO 11007 modified, Water washout	0-1
Corrosion protection, Emcor, ISO 11007 modified, 0.5% NaCl	0-0
Water resistance (max.) DIN 51807/1, 3 hrs at 90 °C	1
Oil separation DIN 51817, 40°C, %	1-5
Lubrication ability, R2F test B at 120°C	Pass
Copper corrosion (max.) DIN 51811 /ASTM D4048, 24 hrs at 100°C	1b max. at 100°C
Rolling bearing grease life (max.) ROF test, L50 life, 10000 r/min, hrs at °C	1000 at 160°C
EP performance - 4 ball - Wear scar (max.) DIN 51350/5, 1400N	2 mm
EP performance - 4 ball - Weld load (min.) DIN 51350/4	2600 N

Properties	
Recommended applications	Electric motors;Industrial fans;Water pumps;Vertical shaft applications
Category	Bearing grease
Lubricant	LGHQ 2
NLGI consistency class	2
Base oil viscosity DIN 51562 at 40 °C	110 mm ² /s
Base oil viscosity DIN 51562 at 100 °C	12 mm ² /s
Biodegradable	No
DIN 51825 code	K2P-30
Thickener	Polyurea
Colour	Blue
Base oil type	Mineral
Shelf life	5 year
Available for single point lubrication	yes

Logistics	
Product net weight	18 kg
eClass code	23-06-01-01
UNSPSC code	15121902