



SKF 16012

Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

Technical specifications

Dimensions	
Bore diameter	60 mm
Deviation limits of mid-range bore diameter	-0.012..0 mm
Outside diameter	95 mm
Deviation limits of mid-range outside diameter	-0.013..0 mm
Width	11 mm
Deviation limits of ring width	-0.06..0 mm
Shoulder diameter	72 mm
Shoulder diameter	83 mm
Chamfer dimension	0.6 mm
ISO tolerance class for dimensions	P6 and tighter width tolerance

Abutment dimensions	
Diameter of shaft abutment	63.2 mm
Diameter of housing abutment	91.8 mm
Radius of shaft or housing fillet	0.6 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	20.8 kN
Basic static load rating	15 kN
Fatigue load limit	0.735 kN
Reference speed	15000 r/min
Limiting speed	9500 r/min
Minimum load factor	0.02
Calculation factor	13.9

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	10 µm
Range of section height at outer ring of assembled bearing	18 µm
ISO tolerance class for geometrical tolerances	P6

Performance	
Basic dynamic load rating	20.8 kN
Basic static load rating	15 kN
Reference speed	15000 r/min
Limiting speed	9500 r/min
SKF performance class	SKF Explorer

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel

Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	1 kg CO ₂ e

Logistics	
Product net weight	0.279 kg
eClass code	23-05-08-01
UNSPSC code	31171504

SKF drawings