



SKF NU 222 ECJ

Single row cylindrical roller bearing, NU design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	110 mm
Outside diameter	200 mm
Width	38 mm
Shoulder diameter of outer ring	172.5 mm
Raceway diameter of inner ring	132.5 mm
Chamfer dimension	2.1 mm
Chamfer dimension	2.1 mm
Permissible axial displacement	2.1 mm

Abutment dimensions	
Diameter of spacer sleeve	122 mm
Diameter of spacer sleeve	129 mm
Diameter of shaft abutment	135 mm
Diameter of housing abutment	187 mm
Radius of fillet	2 mm
Radius of fillet	2 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	335 kN
Basic static load rating	365 kN
Fatigue load limit	42.5 kN
Reference speed	3600 r/min
Limiting speed	4000 r/min
Minimum load factor	0.15
Limiting value	0.2
Calculation factor	0.6

Associated products	
Angle ring	HJ 222 EC

Performance	
Basic dynamic load rating	335 kN
Basic static load rating	365 kN
Reference speed	3600 r/min
Limiting speed	4000 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Number of flanges, outer ring	2
Number of flanges, inner ring	0

Loose flange	None
Radial internal clearance	CN
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	17.3 kg CO ₂ e

Logistics	
Product net weight	4.81 kg
eClass code	23-05-09-01
UNSPSC code	31171505

SKF drawings