



SKF NU 1032 ML

Single row cylindrical roller bearing, NU design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	160 mm
Outside diameter	240 mm
Width	38 mm
Shoulder diameter of outer ring	210.8 mm
Raceway diameter of inner ring	180 mm
Chamfer dimension	2.1 mm
Chamfer dimension	1.5 mm
Permissible axial displacement	5.2 mm

Abutment dimensions	
Diameter of spacer sleeve	167 mm
Diameter of spacer sleeve	177 mm
Diameter of shaft abutment	183 mm
Diameter of housing abutment	230 mm
Radius of fillet	2 mm
Radius of fillet	1.5 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	265 kN
Basic static load rating	325 kN
Fatigue load limit	35.5 kN
Reference speed	3000 r/min
Limiting speed	4800 r/min
Minimum load factor	0.15
Limiting value	0.2
Calculation factor	0.6

Associated products	
Angle ring	HJ 1032

Performance	
Basic dynamic load rating	265 kN
Basic static load rating	325 kN
Reference speed	3000 r/min
Limiting speed	4800 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Machined brass
Number of flanges, outer ring	2
Number of flanges, inner ring	0

Loose flange	None
Radial internal clearance	CN
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	21.5 kg CO ₂ e

Logistics	
Product net weight	5.98 kg
eClass code	23-05-09-01
UNSPSC code	31171505

SKF drawings