



# SKF TMHS 100-1

## Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

### Характеристики

| Логистика                        |                                                                                                                                                                                                                                                    |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Масса нетто                      | 2.62 kg                                                                                                                                                                                                                                            |
| Код eClass                       | 23-05-19-01                                                                                                                                                                                                                                        |
| Код UNSPSC                       | 27111712                                                                                                                                                                                                                                           |
| Свойства                         |                                                                                                                                                                                                                                                    |
| Рекомендуемые применения         | For use as force generator with desingated SKF pullers in the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft. |
| Special features                 | Integrated safety valve; Closed hydraulic system                                                                                                                                                                                                   |
| Pulling force (max)              | 100 kN                                                                                                                                                                                                                                             |
| Hydraulic spindle, piston stroke | 85 mm                                                                                                                                                                                                                                              |
| Connecting thread (G)            | UN 1.5 x 16 tpi                                                                                                                                                                                                                                    |
| Total spindle length             | 495                                                                                                                                                                                                                                                |
| Spindle nose piece               | not included                                                                                                                                                                                                                                       |
| Reach (max)                      | Array mm                                                                                                                                                                                                                                           |
| Материал                         | Alloy engineering steels, hardened and tempered                                                                                                                                                                                                    |
| Покрытие                         | Spindle and handle bar: chrome coated;Spindle body, nose and extention pieces black phosphated                                                                                                                                                     |
| Цвет                             | Metallic and black                                                                                                                                                                                                                                 |
| Recommended storage temperature  | Array °C                                                                                                                                                                                                                                           |
| Relative humidity                | < 75%                                                                                                                                                                                                                                              |
| Content                          | 1× Hydraulic spindle;QR code card                                                                                                                                                                                                                  |