



SKF GE 20 ES

Radial spherical plain bearing, requiring maintenance, metric sizes

Radial spherical plain bearings are designed to accommodate radial and combined radial and axial loads, and also misalignment. This specific design includes a steel/steel sliding contact surface combination. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Without

Dimensions	
Bore diameter	20 mm
Outside diameter	35 mm
Width	16 mm
Width outer ring	12 mm
Angle of tilt	9 °
Raceway diameter inner ring	29 mm
Width annular lubrication groove at outer ring	3.1 mm
Width annular lubrication groove at inner ring	3.2 mm
Diameter lubrication hole (outer ring)	2 mm
Chamfer dimension bore	0.3 mm
Chamfer dimension outer ring	0.3 mm
Width, inner ring	16 mm
Width, outer ring	12 mm

Abutment dimensions	
Abutment diameter shaft	22.1 mm
Abutment diameter shaft	24.2 mm
Abutment diameter housing	27.6 mm
Abutment diameter housing	33.2 mm
Fillet radius shaft	0.3 mm
Fillet radius housing	0.3 mm

Calculation data	
Basic dynamic load rating	30 kN
Basic static load rating	146 kN
Specific dynamic load factor	100 N/mm ²
Specific static load factor	500 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	30 kN
Basic static load rating	146 kN

Properties	
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Radial internal clearance	CN
Sealing	Without

Relubrication feature	With
-----------------------	------

Logistics	
Product net weight	0.0627 kg
eClass code	23-05-01-06
UNSPSC code	31171515

SKF drawings