



SKF 3215 A-2RS1

Double row angular contact ball bearing with seals or shields

Double row angular contact ball bearings, with seals or shields, correspond to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. Depending on the sealing execution, they can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

Technical specifications

| Dimensions | |
|------------------|---------|
| Bore diameter | 75 mm |
| Outside diameter | 130 mm |
| Width | 41.3 mm |
| Contact angle | 30 ° |

| Performance | |
|---------------------------|------------|
| Basic dynamic load rating | 95.6 kN |
| Basic static load rating | 88 kN |
| Reference speed | 5300 r/min |
| Limiting speed | 4500 r/min |

| Properties | |
|---|------------------------------------|
| Contact type | Normal contact (two-point contact) |
| Number of rows | 2 |
| Locating feature, bearing outer ring | Without |
| Ring type | One-piece inner and outer rings |
| Cage | Sheet metal |
| Arrangement of contact angle (double-row bearing) | Back-to-back (O) |
| Matched arrangement | No |
| Universal matching bearing | No |
| Axial internal clearance | CN |
| Material, bearing | Bearing steel |
| Coating | Without |
| Sealing | Seal on both sides |
| Sealing type | Contact |
| Lubricant | Grease |
| Relubrication feature | Without |
| Indicative carbon footprint for new product | 6.6 kg CO ₂ |

| Logistics | |
|--------------------|-------------|
| Product net weight | 1.82 kg |
| eClass code | 23-05-08-03 |
| UNSPSC code | 31171531 |