



SKF 32322

Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

Technical specifications

General	
Dimension series	2GD

Dimensions	
Bore diameter	110 mm
Outside diameter	240 mm
Bearing width, total	84.5 mm
Shoulder diameter of inner ring	168.5 mm
Width of inner ring	80 mm
Width of outer ring	65 mm
Chamfer dimension of inner ring	4 mm
Chamfer dimension of outer ring	3 mm
Distance side face to pressure point	55.355 mm
Width, total	84.5 mm
Width, inner ring	80 mm
Width, outer ring	65 mm
Contact angle	13 °

Abutment dimensions	
Diameter of shaft abutment	138 mm
Diameter of shaft abutment	126.5 mm
Diameter of housing abutment	198 mm
Diameter of housing abutment	227 mm
Diameter of housing abutment	222 mm
Minimum width of space required in housing on large side face	9 mm
Minimum width of space required in housing on small side face	19.5 mm
Radius of shaft fillet	4 mm
Radius of housing fillet	3 mm

Calculation data	
Basic dynamic load rating	675 kN
Basic static load rating	830 kN
Fatigue load limit	86.5 kN
Reference speed	1900 r/min
Limiting speed	2800 r/min
Limiting value	0.35
Calculation factor	1.7
Calculation factor	0.9

Performance	
Basic dynamic load rating	675 kN
Basic static load rating	830 kN
Reference speed	1900 r/min
Limiting speed	2800 r/min

Properties	
Bearing part	Complete bearing
Number of rows	1

Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	59.2 kg CO ₂ e

Logistics	
Product net weight	16.4 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings