



SKF 20X35X7 HMS5 V

Radial shaft seal with rubber outside diameter and single sealing lip, for oil or grease.

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. HMS5 seals are designed with a rubber outside diameter. They have a conventional sealing lip made of elastomer with a garter spring to maintain the right radial load.

Technical specifications

General	
Type of outside diameter	Rubber metal reinforced
Lip material	Fluoro rubber (FKM)
Seal design	HMS5
Compliance with standard	ISO 6194; DIN 3760
Dimensions	
Shaft diameter	20 mm
Housing bore diameter	35 mm
Seal width	7 mm
Application and operating conditions	
Operating temperature	-25 °C
Operating temperature	200 °C
Operating temperature, short periods	200 °C
Circumferential speed	14.9 m/s
Rotational speed	14220 r/min
Pressure differential	0.05 N/mm ²
Associated products	
SKF Speedi-Sleeve	99078
Performance	
Limiting speed	14220 r/min
Maximum operating temperature	200 °C
Minimum operating temperature	-25 °C
Permissible circumferential speed	14.9 m/s
Rotational speed	14220 r/min
Properties	
Design	HMS5
Auxiliary lip	No
Sealing lip material	Fluoro rubber (FKM)
Type of outside diameter	Rubber metal reinforced
Unit system	Metric
Logistics	
Product net weight	0.0096 kg
eClass code	23-07-08-01
UNSPSC code	31181602

SKF drawings