



SKF 61900-2RS1

Deep groove ball bearing with seals or shields

Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

Technical specifications

Dimensions	
Bore diameter	10 mm
Deviation limits of mid-range bore diameter	-0.007..0 mm
Outside diameter	22 mm
Deviation limits of mid-range outside diameter	-0.008..0 mm
Width	6 mm
Deviation limits of ring width	-0.12..0 mm
Recess diameter	19.4 mm
Chamfer dimension	0.3 mm
ISO tolerance class for dimensions	P6

Abutment dimensions	
Diameter of shaft abutment	12 mm
Diameter of shaft abutment	12 mm
Diameter of housing abutment	20 mm
Radius of shaft or housing fillet	0.3 mm

Calculation data	
Basic dynamic load rating	2.7 kN
Basic static load rating	1.27 kN
Fatigue load limit	0.054 kN
Limiting speed	20000 r/min
Minimum load factor	0.02
Calculation factor	14

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	6 µm
Range of section height at outer ring of assembled bearing	9 µm
ISO tolerance class for geometrical tolerances	P6

Performance	
Basic dynamic load rating	2.7 kN
Basic static load rating	1.27 kN
Limiting speed	20000 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	Without

Indicative carbon footprint for new product

0.03 kg CO₂e**Logistics**

Product net weight	0.0096 kg
eClass code	23-05-08-01
UNSPSC code	31171504

SKF drawings