



SKF GE 160 ES

Radial spherical plain bearing, requiring maintenance, metric sizes

Radial spherical plain bearings are designed to accommodate radial and combined radial and axial loads, and also misalignment. This specific design includes a steel/steel sliding contact surface combination. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Without
Dimensions	
Bore diameter	160 mm
Outside diameter	230 mm
Width	105 mm
Width outer ring	80 mm
Angle of tilt	8 °
Raceway diameter inner ring	200 mm
Width annular lubrication groove at outer ring	13.5 mm
Width annular lubrication groove at inner ring	13.5 mm
Diameter lubrication hole (outer ring)	6 mm
Chamfer dimension bore	1 mm
Chamfer dimension outer ring	1 mm
Width, inner ring	105 mm
Width, outer ring	80 mm
Abutment dimensions	
Abutment diameter shaft	169.5 mm
Abutment diameter shaft	170 mm
Abutment diameter housing	190 mm
Abutment diameter housing	222 mm
Fillet radius shaft	1 mm
Fillet radius housing	1 mm
Calculation data	
Basic dynamic load rating	1370 kN
Basic static load rating	6800 kN
Specific dynamic load factor	100 N/mm ²
Specific static load factor	500 N/mm ²
Material constant	330
Performance	
Basic dynamic load rating	1370 kN
Basic static load rating	6800 kN
Properties	
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Radial internal clearance	CN
Sealing	Without

Relubrication feature	With
-----------------------	------

Logistics	
Product net weight	13.8 kg
eClass code	23-05-01-06
UNSPSC code	31171515

SKF drawings