



## SKF 6217/C3VL0241

### INSOCOAT® deep groove ball bearing

INSOCOAT single row deep groove ball bearings feature an electrically insulating coating on the outside surfaces of either the inner or outer bearing ring. This keeps stray electric currents from passing through the bearings, protecting them against electrical erosion damage and helping prevent lubricant degradation resulting from electric current discharge. As with deep groove ball bearings generally, they are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

## Technical specifications

Dimensions	
Bore diameter	85 mm
Outside diameter	150 mm
Width	28 mm
Shoulder diameter inner ring	106.05 mm
Recess diameter outer ring shoulder	134 mm
Chamfer dimension	2 mm

Abutment dimensions	
Abutment diameter shaft	96 mm
Abutment diameter shaft	139 mm
Abutment diameter housing	139 mm
Fillet radius	2 mm

Calculation data	
Basic dynamic load rating	87.1 kN
Basic static load rating	64 kN
Fatigue load limit	2.5 kN
Reference speed	9000 r/min
Limiting speed	5600 r/min
Calculation factor	0.03
Calculation factor	14.7

Performance	
Basic dynamic load rating	87.1 kN
Basic static load rating	64 kN
Reference speed	9000 r/min
Limiting speed	5600 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	C3
Material, bearing	Bearing steel
Coating	Insulation coating on outer ring
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	6.3 kg CO <sub>2</sub>

Logistics	
Product net weight	1.74 kg
eClass code	23-05-08-01
UNSPSC code	31171537

**SKF drawings**