



## SKF 30304

### Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

## Technical specifications

General	
Dimension series	2FB
Dimensions	
Bore diameter	20 mm
Outside diameter	52 mm
Bearing width, total	16.25 mm
Shoulder diameter of inner ring	34.4 mm
Width of inner ring	15 mm
Width of outer ring	13 mm
Chamfer dimension of inner ring	1.5 mm
Chamfer dimension of outer ring	1.5 mm
Distance side face to pressure point	11.15 mm
Width, total	16.25 mm
Width, inner ring	15 mm
Width, outer ring	13 mm
Contact angle	11.3 °
Abutment dimensions	
Diameter of shaft abutment	28 mm
Diameter of shaft abutment	27.5 mm
Diameter of housing abutment	44 mm
Diameter of housing abutment	45.5 mm
Diameter of housing abutment	47 mm
Minimum width of space required in housing on large side face	2 mm
Minimum width of space required in housing on small side face	3 mm
Radius of shaft fillet	1.5 mm
Radius of housing fillet	1.5 mm
Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	41.9 kN
Basic static load rating	32.5 kN
Fatigue load limit	3.55 kN
Reference speed	12000 r/min
Limiting speed	14000 r/min
Limiting value	0.3
Calculation factor	2
Calculation factor	1.1
Performance	
Basic dynamic load rating	41.9 kN
Basic static load rating	32.5 kN
Reference speed	12000 r/min
Limiting speed	14000 r/min
SKF performance class	SKF Explorer
Properties	

Bearing part	Complete bearing
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	0.6 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	0.166 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings

