

# SKF TMMS 100

## Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

## Характеристики

| Логистика   |             |
|-------------|-------------|
| Масса нетто | 2.54 kg     |
| Код eClass  | 23-05-19-01 |
| Код UNSPSC  | 27111712    |

| Свойства                                                                         |                                                                                                                                                                                                                                                                                                                   |
|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Рекомендуемые применения                                                         | For use with a puller in the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft. To assist a three armed puller where the claws of the puller can't grip the component properly. |
| Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)   | Да                                                                                                                                                                                                                                                                                                                |
| Pulling force (max)                                                              | 200 kN                                                                                                                                                                                                                                                                                                            |
| Suitable for bearing dismounting from a Tapered seating (conical shaft)          | Да                                                                                                                                                                                                                                                                                                                |
| Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)    | Да                                                                                                                                                                                                                                                                                                                |
| Connecting thread (G)                                                            | M16x2                                                                                                                                                                                                                                                                                                             |
| Suitable for workpiece dismounting from a Blind arrangement (housing with shaft) | Нет                                                                                                                                                                                                                                                                                                               |
| Suitable for workpiece dismounting from a Housing                                | Нет                                                                                                                                                                                                                                                                                                               |
| Dismounting force generation                                                     | by pullerarms                                                                                                                                                                                                                                                                                                     |
| Section plates provided with threaded pullinghole                                | Да                                                                                                                                                                                                                                                                                                                |
| Материал                                                                         | Alloy engineering steels, hardened and tempered                                                                                                                                                                                                                                                                   |
| Покрытие                                                                         | Rods: black phosphated; Plates and nuts, Zinc coated                                                                                                                                                                                                                                                              |
| Цвет                                                                             | Metallic and black                                                                                                                                                                                                                                                                                                |

| Размеры                         |          |
|---------------------------------|----------|
| Width of grip external          | Array mm |
| Pulling rod distance            | Array mm |
| Distance threaded pulling holes | 34 mm    |
| Plate width                     | 60 mm    |
| Plate height                    | 25 mm    |
| Plate tip width                 | 6 mm     |
| Plate tip height                | 3 mm     |