



SKF FYTWK 25 YTH

Oval flanged ball bearing unit with set screw locking and extended inner ring, co

These oval flanged ball bearing units are designed especially for the food and beverage industries. They are chemical resistant, lightweight and strong. The unit consists of an insert bearing, with an extended inner ring and set screw locking, and is suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a composite housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

Technical specifications

General	
Compliance with standard	ISO with boundary dimension deviations
Purpose specific	For food and beverage applications
Material, housing	Composite for the SKF Food Line
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, multiple
Sealing, unit	Optional end cover
Coating	Without

Dimensions	
Bore diameter	25 mm
Outer diameter of inner ring	33.74 mm
Width of housing	30 mm
Flange width	15 mm
Width including end cover	26 mm
Width of inner ring	34.1 mm
Overall bearing width	34.1 mm
Distance from locking device side face to thread centre	5 mm
Top external diameter	65 mm
Overall height	124 mm
Centre distance between bolt holes	99 mm
Overall length	70 mm
Diameter of attachment bolt hole	12.3 mm
Distance from locking device side face to raceway centre	19.8 mm
Overall width	38.8 mm
Attachment bolt diameter	10 mm
Shaft diameter	25 mm
Housing overall width	30 mm
Bearing width, total	34.1 mm

Calculation data	
Basic dynamic load rating	11.9 kN
Basic static load rating	7.8 kN
Fatigue load limit	0.335 kN
Limiting speed	4300 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M6x0.75
Hexagonal key size for set screw	3 mm
Recommended tightening torque for set screw	4 N·m
Recommended diameter for attachment bolts, mm	10 mm
Recommended diameter for attachment bolts, inch	0.375 in

Performance	
Basic dynamic load rating	11.9 kN
Basic static load rating	7.8 kN
Limiting speed	4300 r/min

Note

Limiting speed with shaft tolerance h6

Properties	
Housing type	Flanged
Flanged housing type	Oval
Number of bolt holes for fasteners	2
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Composite for the SKF Food Line
Material, bearing	Stainless steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, multiple
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	Without
Grease fitting	Without

Logistics	
Product net weight	0.306 kg

SKF drawings

