



SKF TLSD 250/HB2

SKF SYSTEM 24 single point lubricator

TLSD 250/HB2 is filled with SKF LGHB 2 grease for high loads, wet environments and high temperatures, recommended for plain bearings, conveyors and applications with high loads and low speeds. Our electro-mechanical single point automatic lubricators are available in many configurations, pre-filled with SKF lubricants, both as battery or cable driven. Using automatic lubricators improves employee safety, increases machine reliability and optimizes maintenance operations.

Technical specifications

Performance	
Maximum pressure (P _{max})	5 bar
Properties	
Ambient temperature range	Array °C
Connecting thread (G)	G 1/4
Degree of protection (IP)	IP 65
Drive mechanism	Electro mechanical
Lubricant	LGHB 2
Lubricant description	High viscosity, high loads and high temperatures grease
Lubricant operating temperature range	-20 to +150 °C
Lubricant quantity	250 ml
Maximum feed line length	3 m
Nominal emptying time	User adjustable: 1, 2, 3, 4, 6, 8, 10 and 12 months
Power source	Battery pack
Recommended applications	Plain bearings;Conveyors;Applications with high loads and low speed
Logistics	
Product net weight	0.73 kg
eClass code	23-06-10-14
UNSPSC code	15121902