



SKF NU 330 ECM/C4VA301

Single row cylindrical roller bearing, NU design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	150 mm
Outside diameter	320 mm
Width	65 mm

Performance	
Basic dynamic load rating	900 kN
Basic static load rating	965 kN
Reference speed	2200 r/min
Limiting speed	2600 r/min

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Machined brass
Number of flanges, outer ring	2
Number of flanges, inner ring	0
Loose flange	None
Radial internal clearance	C4
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Candidate for remanufacturing	Yes
Indicative carbon footprint for new product	94.7 kg CO ₂ e
Indicative carbon footprint for remanufactured product	33.1 kg CO ₂ e

Logistics	
Product net weight	26.3 kg
eClass code	23-05-09-01
UNSPSC code	31171505