



## SKF 6018

### Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

## Technical specifications

Dimensions	
Bore diameter	90 mm
Deviation limits of mid-range bore diameter	-0.015..0 mm
Outside diameter	140 mm
Deviation limits of mid-range outside diameter	-0.015..0 mm
Width	24 mm
Deviation limits of ring width	-0.1..0 mm
Shoulder diameter	105.95 mm
Recess diameter	128.3 mm
Chamfer dimension	1.5 mm
ISO tolerance class for dimensions	P6 and tighter width tolerance

  

Abutment dimensions	
Diameter of shaft abutment	97 mm
Diameter of housing abutment	133 mm
Radius of shaft or housing fillet	1.5 mm

  

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	60.5 kN
Basic static load rating	50 kN
Fatigue load limit	1.96 kN
Reference speed	10000 r/min
Limiting speed	6300 r/min
Minimum load factor	0.03
Calculation factor	15.6

  

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	25 µm
Range of section height at outer ring of assembled bearing	40 µm
ISO tolerance class for geometrical tolerances	Normal

  

Performance	
Basic dynamic load rating	60.5 kN
Basic static load rating	50 kN
Reference speed	10000 r/min
Limiting speed	6300 r/min
SKF performance class	SKF Explorer

  

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel

Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	4.1 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	1.14 kg
eClass code	23-05-08-01
UNSPSC code	31171504

**SKF drawings**