



SKF 110X140X12 HMS5 V

Radial shaft seal with rubber outside diameter and single sealing lip, for oil or grease.

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. HMS5 seals are designed with a rubber outside diameter. They have a conventional sealing lip made of elastomer with a garter spring to maintain the right radial load.

Technical specifications

General	
Type of outside diameter	Rubber metal reinforced
Lip material	Fluoro rubber (FKM)
Seal design	HMS5
Compliance with standard	ISO 6194; DIN 3760

Dimensions	
Shaft diameter	110 mm
Housing bore diameter	140 mm
Seal width	12 mm

Application and operating conditions	
Operating temperature	-25 °C
Operating temperature	200 °C
Operating temperature, short periods	200 °C
Circumferential speed	34 m/s
Rotational speed	5940 r/min
Pressure differential	0.05 N/mm ²

Associated products	
SKF Speedi-Sleeve	99434

Performance	
Limiting speed	5940 r/min
Maximum operating temperature	200 °C
Minimum operating temperature	-25 °C
Permissible circumferential speed	34 m/s
Rotational speed	5940 r/min

Properties	
Design	HMS5
Auxiliary lip	No
Sealing lip material	Fluoro rubber (FKM)
Type of outside diameter	Rubber metal reinforced
Unit system	Metric

Logistics	
Product net weight	0.117 kg
eClass code	23-07-08-01
UNSPSC code	31181602

SKF drawings

