



SKF SA 8 E

Rod end, requires maintenance, male thread

These SKF rod ends contain a spherical plain bearing with a steel/steel sliding contact surface combination. The bearing requires maintenance and can be relubricated only from the side. The male thread is available with a left- (prefix SAL) or right-hand thread.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Without
Attachment feature, rod end shank	Right-hand male thread

Dimensions	
Bore diameter	8 mm
Diameter head	25 mm
Width inner ring	8 mm
Thread	M 8
Width head	6.5 mm
Height shank end face - centre rod end eye	42 mm
Angle of tilt	15 °
Raceway diameter inner ring	13 mm
Length thread	21 mm
Length (height) housing	56 mm
Distance shank chamfer - centre rod end eye	11 mm
Chamfer dimension bore	0.3 mm
Bore diameter, bearing inner ring	8 mm
Outside diameter, housing eye	25 mm
Width, bearing inner ring	8 mm
Thread designation	M 8
Width, housing eye	6.5 mm
Centre height, housing (from end of shank)	42 mm
Housing length, total	56 mm

Calculation data	
Basic dynamic load rating	5.5 kN
Basic static load rating	12.9 kN
Specific dynamic load factor	100 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	5.5 kN
Basic static load rating	12.9 kN

Properties	
Sliding contact surface combination	Steel/steel, standard
Material, housing	Steel
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Attachment feature, rod end shank	Right-hand male thread
Sealing	Without

Logistics	
Product net weight	0.0306 kg
eClass code	23-05-01-05
UNSPSC code	31171508

SKF drawings

