



SKF QJ 205 N2MA/C2L

Four-point contact ball bearing with locating slots

Four-point contact ball bearings with locating slots can accommodate high axial loads in both directions and small radial loads. They can operate at very high speeds and are more suitable than deep groove ball bearings for supporting large axial forces. The outer ring, with ball and cage assembly, can be mounted separately from the two inner ring halves. The locating slots can be used to prevent the outer ring from rotating.

Technical specifications

Dimensions	
Bore diameter	25 mm
Outside diameter	52 mm
Width	15 mm
Contact angle	35 °

Performance	
Basic dynamic load rating	27 kN
Basic static load rating	21.2 kN
Limiting speed	22000 r/min
SKF performance class	SKF Explorer

Properties	
Contact type	Four-point contact
Number of rows	1
Locating feature, bearing outer ring	Locating slot
Ring type	Two-piece inner ring and one-piece outer ring
Cage	Machined brass
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	C2L
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.57 kg CO ₂ e

Logistics	
Product net weight	0.158 kg
eClass code	23-05-08-05
UNSPSC code	31171538