



## SKF 65X85X8 CRW1 V

Radial shaft seal with metal case and SKF Wave lip, for oil or grease

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. CRW1 seals are designed with a metal case, an SKF WAVE lip made of elastomer with higher pumping rate to reduce heat generation, and a garter spring to optimize sealing against the shaft. Most of the seals feature the SKF Bore Tite coating on the outside diameter that helps fill small imperfections in the housing bore.

### Technical specifications

| General                  |                                                          |
|--------------------------|----------------------------------------------------------|
| Type of outside diameter | Metal-cased with sealant coating on the outside diameter |
| Lip material             | Fluoro rubber (FKM)                                      |
| Seal design              | CRW1                                                     |

| Dimensions            |       |
|-----------------------|-------|
| Shaft diameter        | 65 mm |
| Housing bore diameter | 85 mm |
| Seal width            | 8 mm  |

| Application and operating conditions |                        |
|--------------------------------------|------------------------|
| Operating temperature                | -25 °C                 |
| Operating temperature                | 200 °C                 |
| Circumferential speed                | 28 m/s                 |
| Rotational speed                     | 8280 r/min             |
| Pressure differential                | 0.07 N/mm <sup>2</sup> |

| Associated products |       |
|---------------------|-------|
| SKF Speedi-Sleeve   | 99254 |

| Performance                       |            |
|-----------------------------------|------------|
| Limiting speed                    | 8280 r/min |
| Maximum operating temperature     | 200 °C     |
| Minimum operating temperature     | -25 °C     |
| Permissible circumferential speed | 28 m/s     |
| Rotational speed                  | 8280 r/min |

| Properties               |                                                          |
|--------------------------|----------------------------------------------------------|
| Design                   | CRW1                                                     |
| Auxiliary lip            | No                                                       |
| Sealing lip material     | Fluoro rubber (FKM)                                      |
| Type of outside diameter | Metal-cased with sealant coating on the outside diameter |
| Unit system              | Metric                                                   |

| Logistics          |             |
|--------------------|-------------|
| Product net weight | 0.042 kg    |
| eClass code        | 23-07-08-01 |
| UNSPSC code        | 31181602    |

# SKF drawings

