



SKF UCF 209/H

Square flanged ball bearing unit with set screw locking, cast iron housing, JIS

These square flanged ball bearing units are compliant with Japanese Industrial Standards (JIS). They consist of an insert bearing, with an extended inner ring and set screw locking, and are suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a cast iron housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

Technical specifications

General	
Compliance with standard	JIS
Purpose specific	For material handling applications
Material, housing	Cast iron
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Optional end cover
Coating	Without

Dimensions	
Bore diameter	45 mm
Outer diameter of inner ring	56.8 mm
Width of housing	38 mm
Flange width	16 mm
Standout of end cover	26.5 mm
Width of inner ring	49.2 mm
Distance from locking device side face to thread centre	8 mm
Top external diameter	108 mm
Centre distance between bolt holes	105 mm
Overall length	137 mm
Diameter of attachment bolt hole	16 mm
Distance from locking device side face to raceway centre	30.2 mm
Overall width	52.2 mm
Housing thread for grease fitting	1/4-28 UNF
Axial position of the housing thread	26 mm
Diameter of head sphere of grease fitting	6.6 mm
Hexagonal key size for the grease fitting	7.94 mm
Thread of grease fitting	1/4-28 UNF
Attachment bolt diameter	14 mm
Shaft diameter	45 mm
Housing overall width	38 mm
Width, total	52.2 mm
Bearing width, total	49.2 mm

Calculation data	
Basic dynamic load rating	33.2 kN
Basic static load rating	21.6 kN
Fatigue load limit	0.915 kN
Limiting speed	3400 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M8x1
Hexagonal key size for set screw	4 mm
Recommended tightening torque for set screw	6.5 N·m
Recommended diameter for attachment bolts, mm	14 mm
Recommended diameter for attachment bolts, inch	0.5625 in

Performance	
Basic dynamic load rating	33.2 kN
Basic static load rating	21.6 kN
Limiting speed	3400 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Housing type	Flanged
Flanged housing type	Square
Number of bolt holes for fasteners	4
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics	
Product net weight	2.04 kg

SKF drawings

